

MATERIAL		RIGID	FLEXIBLE	QUICK SHIP*	GUARANTEE	UV RESISTANCE	TEMPERATURE RANGE	MAXIMUM REC. SIZE	HOLES	PAGE NO.
PLASTIC	Accu-Shield™ (XP)	✓			15 Year	15	-60° to 260°F	48" x 96"	✓	12
	Accu-Shield™ FB-X	✓			15 Year	15	-60° to 212°F	48" x 96"	✓	12
	Reflecta-Shield™	✓			10 Year	10	-30° to 200°F	48" x 72"	✓	13
	Lumi-Shield™	✓				5 - 7	-30° to 175°F	24" x 36"	✓	13
	Plastic (VP)	✓		✓		1 - 3	-90° to 168°F	36" x 48"	✓	14
	Plastic-Lite	✓				3 - 5	0 to 160°F	48" x 96"	✓	14
	Plastic Plus	✓				1 - 3	-90° to 168°F	48" x 96"	✓	14
	Dura-Plastic™ (XT)	✓			7 Year	7	-40° to 251°F	24" x 36"	✓	15
	Dura-Shield™	✓				4 - 5	-40° to 175°F	24" x 36"	on request	15
	Lumi-Glow™ Plastic (GP)	✓				3	-20° to 149°F	24" x 48"	✓	17
	Lumi-Glow™ Plus+ Plastic	✓				3 - 5	-50° to 190°F	48" x 96"	✓	17
	Lite Corrugated Plastic	✓				1 - 2	-17° to 160°F	24" x 36"	on request	16
	Max Corrugated Plastic	✓				1 - 2	0 to 140°F	48" x 96"	on request	16
	METAL	Aluminum (VA)	✓		✓	5 Year	5	-40° to 140°F	48" x 96"	✓
Heavy-Duty, Max-Duty Aluminum		✓			5 Year	5	-40° to 250°F	48" x 96"	✓	18
Engineer-Grade Prismatic Reflective Aluminum		✓			5 Year	5 - 7	-30° to 200°F	36" x 48"	✓	19
High-Intensity, DG High-Prism Reflective Aluminum		✓			7 Year	7 - 10	-30° to 200°F	36" x 48"	✓	19
Heavy-Duty Engineer-Grade Prismatic Reflective Aluminum		✓			5 Year	5	-40° to 180°F	48" x 96"	✓	20
Diamond Plate Aluminum		✓			5 Year	5	-40° to 176°F	36" x 48"	✓	20
Dura Lumi-Glow™ Aluminum		✓			5 Year	5	-30° to 175°F	24" x 36"	✓	21
Galvanized Steel		✓			5 Year	5	-40° to 250°F	48" x 96"	✓	21
Perma-Black™ Aluminum		✓			10 Year	10	up to 700°F	20" x 24"	✓	23
Perma-Black™ Stainless Steel		✓			15 Year	15	up to 750°F	20" x 24"	✓	23
Stainless Steel		✓			10 Year	10	up to 200°F	9" x 12"	✓	22
St² Laser Signs™	✓			Lifetime	Lifetime	up to 2000°F	14" x 20"	✓	22	
COMPOSITE	Aluma-Lite™ (XL)	✓		✓	10 Year	10	-58° to 175°F	48" x 96"	✓	24
	Ultra Aluma-Lite™	✓			10 Year	10	-58° to 175°F	48" x 96"	on request	24
	Max Aluma-Wood	✓				3 - 5	-30° to 200°F	48" x 96"	on request	24
FIBER-GLASS	Dura-Fiberglass™ (XF)	✓			10 Year	10	-40° to 212°F	48" x 96"	✓	25
ADHESIVE	Lumi-Glow™ Flex (GF)		✓			3	-30° to 175°F	24" x 36"		27
	Lumi-Glow™ Plus+ Flex		✓		5 Year	5	-20° to 125°F	24" x 36"		27
	Adhesive Vinyl (VS)		✓	✓		2	-20° to 176°F	36" x 48"		26
	Adhesive Dura-Vinyl™ (XV)		✓		5 Year	5	-20° to 176°F	36" x 48"		26
	Engineer-Grade Prismatic Adhesive Sheet		✓		5 Year	5 - 7	-30° to 200°F	36" x 48"		28
	High-Intensity Prismatic Adhesive Sheet		✓		7 Year	7 - 10	-30° to 200°F	36" x 48"		28
NON-ADHESIVE	PF-Poly Paper		✓			6 mos.	-60° to 200°F	18" x 24"		29
	Magnetic Co-Poly Vinyl		✓			2 - 4	0 to 160°F	24" x 48"		29